



fcgraphics4mesh Matlab toolbox, User's Guide*

version 0.1.2

François Cuvelier[†]

March 7, 2020

Abstract

This Matlab toolbox allows to display simplicial meshes or datas on simplicial meshes. A simplicial mesh must be given by two arrays : the vertices array and the connectivity array.

0 Contents

1	Introduction	2
2	Installation	3
2.1	Installation automatic, all in one (recommended)	3
2.2	Manual installation	4
3	Mesh	4
4	<code>fc_graphics4mesh.plotmesh</code> function	5
5	<code>fc_graphics4mesh.plot</code> function	9

*LATEX manual, revision 0.1.2, compiled with Matlab 2019a, and toolboxes `fc-graphics4mesh`[0.1.2], `fc-tools`[0.0.31], `fc-bench`[0.1.2], `fcamat`[0.1.2], `fc-meshtools`[0.1.3]

[†]LAGA, UMR 7539, CNRS, Université Paris 13 - Sorbonne Paris Cité, Université Paris 8, 99 Avenue J-B Clément, F-93430 Villetaneuse, France, cuvelier@math.univ-paris13.fr.

This work was supported by the ANR project DEDALES under grant ANR-14-CE23-0005.

6	<code>fc_graphics4mesh.plotiso</code> function	13
7	<code>fc_graphics4mesh.slicemesh</code> function	16
8	<code>fc_graphics4mesh.slice</code> function	17
9	<code>fc_graphics4mesh.sliceiso</code> function	18
10	<code>fc_graphics4mesh.plotquiver</code> function	21
11	<code>fc_graphics4mesh.plotnodes</code> function	24
12	<code>fc_graphics4mesh.plotnodesidx</code> function	27
13	<code>fc_graphics4mesh.plotelementsidx</code> function	30

1 Introduction

The **experimental** Matlab toolbox uses internal functions for displaying simplicial meshes or datas on simplicial meshes. Simplicial meshes could be:

- a triangular mesh in dimension 2, made with 2-simplices (ie. triangles),
- a tetrahedral mesh in dimension 3, made with 3-simplices (ie. tetrahedron),
- a triangular mesh in dimension 3 (surface mesh), made with 2-simplices,
- a line mesh in dimension 2 or 3 made with 1-simplices (ie. lines).

A simplicial mesh is given by its vertices array `q` and its connectivity array `me`. For demonstration purpose, some simplicial meshes are given in this package. They can be load by using the function `getMesh2D`, `getMesh3D` or `getMesh3Ds` of the `fc_graphics4mesh` package.

This toolbox was tested on various OS with Matlab releases:

Operating system	2017a	2017b	2018a	2018b	2019a
CentOS 7.7.1908	✓	✓	✓	✓	✓
Debian 9.11	✓	✓	✓	✓	✓
Fedora 29	✓	✓	✓	✓	✓
OpenSUSE Leap 15.0	✓	✓	✓	✓	✓
Ubuntu 18.04.3 LTS	✓	✓	✓	✓	✓
MacOS High Sierra 10.13.6	✓	✓	✓	✓	✓
MacOS Mojave 10.14.4	✓	✓	✓	✓	✓
MacOS Catalina 10.15.2	✓	✓	✓	✓	✓
Windows 10 (1909)	✓	✓	✓	✓	✓

It is not compatible with Matlab releases prior to R2015b.

2 Installation

2.1 Installation automatic, all in one (recommended)

For this method, one just have to get/download the install file

```
mfc_graphics4mesh_install.m
```

or get it on the dedicated web page. Thereafter, one run it under Matlab. This command download, extract and configure the *fc-graphics4mesh* and the required *fc-tools* toolbox in the current directory.

For example, to install this toolbox in `~/Matlab` directory, one have to copy the file `mfc_graphics4mesh_install.m` in the `~/Matlab` directory. Then in a Matlab terminal run the following commands

```
>> cd ~/Matlab  
>> mfc_graphics4mesh_install
```

There is the output of the `mfc_graphics4mesh_install` command on a Linux computer:

```
Parts of the <fc-graphics4mesh> Matlab toolbox.  
Copyright (C) 2017-2020 F. Cuvelier  
  
1- Downloading and extracting the toolboxes  
2- Setting the <fc-graphics4mesh> toolbox  
Write in ...  
    ~/Matlab/fc-graphics4mesh-full/fc_graphics4mesh-0.1.2/configure_loc.m ...  
...  
3- Using toolboxes :  
    ->           fc-tools : 0.0.31  
    ->           fc-bench : 0.1.2  
    ->           fc-amat : 0.1.2  
    ->           fc-meshtools : 0.1.3  
with     fc-graphics4mesh : 0.1.2  
*** Using instructions  
To use the <fc-graphics4mesh> toolbox:  
addpath('~/Matlab/fc-graphics4mesh-full/fc_graphics4mesh-0.1.2')  
fc_graphics4mesh.init()  
  
See ~/Matlab/mfc_graphics4mesh_set.m
```

The complete toolbox (i.e. with all the other needed toolboxes) is stored in the directory `~/Matlab/fc-graphics4mesh-full` and, for each Matlab session, one have to set the toolbox by:

```
>> addpath('~/Matlab/fc-graphics4mesh-full/fc_meshtools.0.1.2')  
>> fc_graphics4mesh.init()
```

If it's the first time the `fc_meshtools.init()` function is used, then its output is

```

Try to use default parameters!
  Use fc_tools.configure to configure.
Write in ...
  /home/cuvelier/tmp/fc-graphics4mesh-full/fc_tools-0.0.31/configure_loc.m ...
...
Try to use default parameters!
  Use fc_bench.configure to configure.
Write in ...
  /home/cuvelier/tmp/fc-graphics4mesh-full/fc_bench-0.1.2/configure_loc.m ...
...
Try to use default parameters!
  Use fc_amat.configure to configure.
Write in ...
  /home/cuvelier/tmp/fc-graphics4mesh-full/fc_amat-0.1.2/configure_loc.m ...
...
Try to use default parameters!
  Use fc_meshtools.configure to configure.
Write in ...
  /home/cuvelier/tmp/fc-graphics4mesh-full/fc_meshtools-0.1.3/configure_loc.m ...
...
Using fc_graphics4mesh[0.1.2] with fc_tools[0.0.31], fc_bench[0.1.2], ...
  fc_amat[0.1.2], fc_meshtools[0.1.3].

```

Otherwise, the output of the `fc_meshtools.init()` function is

```

Using fc_graphics4mesh[0.1.2] with fc_tools[0.0.31], fc_bench[0.1.2], ...
  fc_amat[0.1.2], fc_meshtools[0.1.3].

```

For **uninstalling**, one just have to delete directory

```

~/Matlab/fc-graphics4mesh-full

```

2.2 Manual installation

This package uses the `fc_mesh` toolbox. So one has to install it as explain in the dedicated web page.

Thereafter, on the `fc_graphics4mesh` dedicated web page, one can found link to archives (`zip`, `7z` or `tar.gz` format)

- Downloads an archive and extract it on a folder, for example `~/Matlab`.
The toolbox path is `~/Matlab/mfc-graphics4mesh-0.1.2`
- Adds the toolbox path in Matlab with `addpath` command.
- Verifies that the `fc_tools`, `fc_bench`, `fc_amat` and `fc_meshtools` toolboxes are in the Matlab path. Otherwise, adds it...

3 Mesh

The functions `getMesh2D`, `getMesh3D` and `getMesh3Ds` return a mesh vertices array `q`, a mesh elements connectivity array associated with the input argument `d` (simplex dimension) and the indices array `toGlobal`. The vertices array `q` is a `dim`-by-`nq` array where `dim` is the space dimension (2 or 3) and `nq` the number of vertices. The connectivity array `me` is a `(d + 1)`-by-`nme` array where `nme` is the number of mesh elements and $0 \leq d \leq dim$ is the simplicial dimension:

- $d = 0$: points,

- $d = 1$: lines,
- $d = 2$: triangle,
- $d = 3$: tetrahedron.

So we can use theses functions to obtain

- 3D mesh: `getMesh3D(3)` (*main* mesh), `getMesh3D(2)`, `getMesh3D(1)`, `getMesh3D(0)`,
- 3D surface mesh: `getMesh3Ds(2)` (*main* mesh), `getMesh3Ds(1)`, `getMesh3Ds(0)`,
- 2D mesh: `getMesh2D(2)` (*main* mesh), `getMesh2D(1)`, `getMesh2D(0)`.

For example,

- `[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMesh3D(3)` return a 3-simplicial mesh (*main* mesh) in space dimension $dim = 3$,
- `[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh3D(2)` return a 2-simplicial mesh in space dimension $dim = 3$.

The third output are indices of the vertices in the *main* mesh:

`q3(:,toGlobal2) == q2`

4 fc_graphics4mesh.plotmesh function

The function `fc_graphics4mesh.plotmesh` displays a mesh given by

Syntaxe

```
fc_graphics4mesh.plotmesh(q,me)
fc_graphics4mesh.plotmesh(q,me,Name,Value, ...)
```

Description

`plotmesh(q,me)` displays all the $\text{Th}.\text{d}$ -dimensional simplices elements.

`plotmesh(q,me,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- `'color'` : to specify the color of the displayed mesh elements. (default : `'blue'`),
- `'cutPlane'` : (only for simplices in dimension 3) cut mesh by n planes given by n -by-4 array P where the equation of the i -th cut plane is given by

$$P(i,1)x + P(i,2)y + P(i,3)z + P(i,4) = 0.$$

The normal vector $P(i,1 : 3)$ pointed to the part of the mesh not displayed. default : `[]` (no cut).

- `'inLegend'` : to add this mesh in a legend if `true`. Default is `false`.


- `'DisplayName'` : to specify the name used in a legend for this mesh.
Then the (`'inLegend'`) option is forced to `true`.

The options of second level depend on the type of elementaries mesh elements to represent.

One can use any option of the following functions according to the type of d -simplex to be represented.

- In dimension 3,
 - if $d == 3$, `patch` function is used,
 - if $d == 2$, `trimesh` function is used,
 - if $d == 1$, `plot3` function is used,
 - if $d == 0$, `plot3` function is used,
- In dimension 2,
 - if $d == 2$, `trimesh` or `patch` function is used,
 - if $d == 1$, `plot` function is used,
 - if $d == 0$, `plot` function is used,
- In dimension 1,
 - if $d == 1$, `line` function is used,
 - if $d == 0$, `plot` function is used,

2D example : the following code is part of the `fc_graphics4mesh.demos.plotmesh2D` function.




```
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh2D(2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh2D(1);
[q0,me0,toGlobal0]=fc_meshtools.simplicial.getMesh2D(0);
figure(1)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray','DisplayName','2-simplex')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black','DisplayName','1-simplex')
fc_graphics4mesh.plotmesh(q0,me0,'color','red','DisplayName','0-simplex')
axis image
legend show


figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'fill',true,'Color','LightGray')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black','Linewidth',2, ...
'DisplayName','1-simplex')
fc_graphics4mesh.plotmesh(q0,me0,'color','red','markersize',8, ...
'DisplayName','0-simplex')
axis image;axis off
```

Listing 1: Using `fc_graphics4mesh.plotmesh` function with a 2D mesh

3Ds example : the following code is part of the `fc_graphics4mesh.demos.plotmesh3Ds` function.



3D example : the following code is part of the `fc_graphics4mesh.demos.plotmesh3D` function.



```
[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMesh3D(3);
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh3D(2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh3D(1);
[q0,me0,toGlobal0]=fc_meshtools.simplicial.getMesh3D(0);
figure(1)
view(3)
fc_graphics4mesh.plotmesh(q3,me3,'EdgeColor','blue','FaceColor','None',...
'DisplayName','3-simplex')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black')
axis image
legend show

figure(2)
view(3)
fc_graphics4mesh.plotmesh(q2,me2,'EdgeColor','LightGray','FaceColor','None',...
'DisplayName','2-simplex')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black','DisplayName','1-simplex')
fc_graphics4mesh.plotmesh(q0,me0,'color','red','DisplayName','0-simplex')
axis image;axis off
legend show

P=[fc_tools.graphics.PlaneCoefs([0 0 1], [0 0 1]); ...
fc_tools.graphics.PlaneCoefs([0 0 1],[-1 0 0])];
figure(3)
fc_graphics4mesh.plotmesh(q1,me1,'color','black')
hold on
fc_graphics4mesh.plotmesh(q3,me3,'cutPlane',P,'Color','DarkGrey',...
'DisplayName','3-simplex')
fc_graphics4mesh.plotmesh(q2,me2,'cutPlane',P,'Color','red',...
'DisplayName','2-simplex')
axis image;axis off
legend show

P=fc_tools.graphics.PlaneCoefs([0 0 1], [-1 0 0]);
figure(4)
fc_graphics4mesh.plotmesh(q1,me1,'color','black')
hold on
fc_graphics4mesh.plotmesh(q3,me3,'cutPlane',P,'Color','DarkGrey')
fc_graphics4mesh.plotmesh(q2,me2,'cutPlane',P,'Color','red')
```

Listing 3: Using `fc_graphics4mesh.plotmesh` function with a 3D mesh

5 `fc_graphics4mesh.plot` function

The function `fc_graphics4mesh.plot` displays data on a mesh given by its vertices array `q` and its connectivity array `me`.

Syntax

```
fc_graphics4mesh.plot(q,me,u)
fc_graphics4mesh.plot(q,me,u,Name,Value, ...)
```

Description

`plot(q,me,u)` displays data `u` on a simplicial mesh. The data `u` can be an handle function or an array.

`plot(q,me,u,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- '`cutPlane`' : (only for simplices in dimension 3) cut mesh by n planes given by n -by-4 array P where the equation of the i -th cut plane is given by

$$P(i,1)x + P(i,2)y + P(i,3)z + P(i,4) = 0.$$


The normal vector $P(i,1 : 3)$ pointed to the part of the mesh not displayed. default : `[]` (no cut).

The options of second level depend on the type of elementaries mesh elements to represent.


One can use any option of the following functions according to the type of d -simplex to be represented.

- In dimension 3, `patch` function is used.
- In dimension 2,
 - if $d == 2$, `surf` or `patch` (option '`plane`' to `true`) function is used,
 - if $d == 1$, `patch` function is used,
- In dimension 1, `plot` function is used.

2D example : the following code is part of the `fc_graphics4mesh.demos.plot2D` function.



3Ds example : the following code is part of the `fc_graphics4mesh.demos.plot3Ds` function.




```

u=@(x,y,z) cos(x).*cos(y).*cos(z);
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh3Ds(2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh3Ds(1);
U2=fc_meshtools.eval(u,q2);
U1=fc_meshtools.eval(u,q1);
figure(1)
fc_graphics4mesh.plot(q2,me2,U2)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)
shading interp
axis image;axis off
colorbar
figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray')
hold on
fc_graphics4mesh.plot(q1,me1,U1,'LineWidth',2)
axis image;axis off
caxis([min(U2),max(U2)])
colorbar
P=fc_tools.graphics.PlaneCoefs([0 0 0], [0 0 1]);
figure(3)
fc_graphics4mesh.plot(q2,me2,U2,'cutPlane',P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)
shading interp
axis image;axis off
caxis([min(U2),max(U2)])
colorbar
figure(4)
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray','cutPlane',P)
hold on
fc_graphics4mesh.plot(q1,me1,U1,'LineWidth',2,'cutPlane',P)
axis image;axis off
caxis([min(U2),max(U2)])

```

Listing 5: Using `fc_graphics4mesh.plot` function with a 3Ds mesh

3D example : the following code is part of the `fc_graphics4mesh.demos.plot3D` function.



```

u=@(x,y,z) cos(x).*sin(y+z);
[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMeshArrays('3D',3);
U3=fc_meshtools.eval(u,q3);
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMeshArrays('3D',2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('3D',1);

figure(1)
fc_graphics4mesh.plot(q3,me3,U3)
shading interp
axis image; axis off
colorbar

figure(2)
fc_graphics4mesh.plot(q2,me2,U3(toGlobal2))
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black','LineWidth',2)
shading interp
axis image; axis off
caxis([min(U3),max(U3)])
colorbar

figure(3)
fc_graphics4mesh.plotmesh(q2,me2,'EdgeColor','LightGray','FaceColor','None')
hold on
fc_graphics4mesh.plot(q1,me1,u,'LineWidth',2)
axis image; axis off
caxis([min(U3),max(U3)])
colorbar

P=[fc_tools.graphics.PlaneCoefs([0.2 0 1], [1 0 ...
    0]);fc_tools.graphics.PlaneCoefs([-0.2 0 1], [-1 0 0])];
figure(4)
fc_graphics4mesh.plot(q2,me2,U3(toGlobal2),'cutPlane',P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','black','LineWidth',2)
shading interp
axis image; axis off
caxis([min(U3),max(U3)])

```

Listing 6: Using `fc_graphics4mesh.plot` function with a 3D mesh

6 fc_graphics4mesh.plotiso function

The function `fc_graphics4mesh.plot` displays isolines from datas on a 2-simplicial mesh given by its vertices array `q` and its connectivity array `me`.

Syntax

```
fc_graphics4mesh.plotiso(q,me,u)
fc_graphics4mesh.plotiso(q,me,u,Name,Value, ...)
```

Description

`plotiso(q,me,u)` displays isolines from datas on the 2-simplicial mesh given by the vertices array `q` and the connectivity array `me`. The data `u` can be an handle function or an array.

`plotiso(q,me,u,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- `'niso'` : to specify the number of isolines (default : 10)
- `'isorange'` : to specify the list of isovalues (default : empty)
- `'isocolorbar'` : if `true`, colorbar with isovalues is drawn (default : `false`)
- `'format'` : to specify the format of the isovalues on the colorbar (default : `'%g'`)
- `'plane'` : if `true`, isolines are in the *xy*-plane, otherwise isolines are in 3D with *z*-value set to `u` (default : `false`)
- `'color'` : to specify one color for all isolines (default : empty)
- `'mouse'` : if `true`, display information on clicked isoline (default : `true`)


The options of second level are all options of

- `plot3` function in dimension 3 or in dimension 2 with `'plane'` option set to `false`
- `plot` function in 2 with `'plane'` option set to `true`


This function accepts until 3 output arguments :

- 1st output is the colors of the isolines
- 2nd output is the isovalues of the isolines
- 3th output is all the handles of the isolines as an 2D-array of dimension N-by-niso, where N is the number of 2-simplex elementary meshes where isolines are drawn.


2D example : the following code is part of the `fc_graphics4mesh.demos.plotiso2D` function.



3Ds example : the following code is part of the `fc_graphics4mesh.demos.plotiso3Ds` function.



3D example : the following code is part of the `fc_graphics4mesh.demos.plotiso3D` function.



Listing 9: Using `fc_graphics4mesh.plotiso` function with a 3D mesh

7 `fc_graphics4mesh.slicemesh` function

The `fc_graphics4mesh.slicemesh` function displays intersection of a plane and a 3D mesh given by its vertices array `q` and its connectivity array `me`.

Syntaxe

```

fc_graphics4mesh.slicemesh(q,me,P)
fc_graphics4mesh.slicemesh(q,me,P,Name,Value, ...)

```

Description


`slicemesh(q,me,P)` displays intersection of the plane defined by $P(1)x + P(2)y + P(3)z + P(4) = 0$ and all the 3-dimensional simplices elements given by `q` and `me` arrays. To compute `P` one can use the `fc_tools.graphics.PlaneCoefs` function of the `FC-TOOLS` toolbox. The 1-by-4 array `P`, is obtained with `P=fc_tools.graphicsPlaneCoefs(Q,V)` where `Q` is a point in the plane and `V` is a vector orthogonal to it. One can also used a n -by-4 array `P` where each line define a plane.

`slicemesh(q,me,P,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- 'color' : to specify the slice color (default : 'LightGray', $\text{rgb}=[0.9,0.9,0.9]$)

The options of second level are all options of the **patch** function except 'FaceColor' and 'EdgeColor'

3D example : the following code is part of the `fc_graphics4mesh.demos.slicemesh3D` function.



```
[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMeshArrays('3D',3);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('3D',1);
figure(1)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 0 0]);%
fc_graphics4mesh.slicemesh(q3,me3,P,'DisplayName','slice1')
hold on
P=fc_tools.graphics.PlaneCoefs([0 0 1],[0 1 0]);%
fc_graphics4mesh.slicemesh(q3,me3,P,'Color','DarkRed','DisplayName','slice2')
P=fc_tools.graphics.PlaneCoefs([0 0 1],[0 0 1]);%
fc_graphics4mesh.slicemesh(q3,me3,P,'Color','Olive','DisplayName','slice2')
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)
axis off; axis image
legend('show')
figure(2)
P=fc_tools.graphics.PlaneCoefs([0 0 1/2],[1 0 0]); ...
fc_tools.graphics.PlaneCoefs([0 0 1/2],[0 1 0]); ...
fc_tools.graphics.PlaneCoefs([0 0 1/2],[0 -1 1]);
fc_graphics4mesh.slicemesh(q3,me3,P,'Color',{ 'Purple','DarkRed','Olive'}, ...
'DisplayName',{ 'slice1','slice2','slice3'})
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)
axis off; axis image
```

Listing 10: Using `fc_graphics4mesh.slicemesh` function with a 3D mesh

8 `fc_graphics4mesh.slice` function

The `fc_graphics4mesh.slice` function displays intersection of a plane and a 3D mesh given by its vertices array q and its connectivity array me.

Syntaxe


```
fc_graphics4mesh.slice(q,me,u,P)
fc_graphics4mesh.slice(q,me,u,P,Name,Value, ...)
```

Description

slice(q,me,u,P) displays data on the intersection of the plane defined by $P(1)x + P(2)y + P(3)z + P(4) = 0$ and all the 3-dimensional simplices elements given by q and me arrays. To compute P one can use the `fc_tools.graphics.PlaneCoefs` function of the `FC-TOOLS` toolbox. The array P , is obtained with $P=fc_tools.graphicsPlaneCoefs(Q,V)$ where Q is a point in the plane and V is a vector orthogonal to it. One can also used a n -by-4 array P where each line define a plane.

slice(q,me,u,P,Name,Value, ...) specifies function options using one or more `Name,Value` pair arguments which are those of the `patch` function excepts '`FaceColor`' and '`EdgeColor`'.

3D example : the following code is part of the `fc_graphics4mesh.demos.slice3D` function.



```

u=@(x,y,z) 2*cos(x).*sin(y+z);
[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMeshArrays('3D',3);
U3=fc_meshtools.eval(u,q3);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('3D',1);

figure(1)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 0 0]);
fc_graphics4mesh.slicemesh(q3,me3,P)
hold on
fc_graphics4mesh.slice(q3,me3,U3,P)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[0 1 0]);
fc_graphics4mesh.slice(q3,me3,U3,P)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[0 0 1]);%
fc_graphics4mesh.slice(q3,me3,U3,P)
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)
axis off; axis image
colorbar

figure(2)
P=[fc_tools.graphics.PlaneCoefs([0 0 1],[1 0 0]); ...
    fc_tools.graphics.PlaneCoefs([0 0 1],[0 1 0]); ...
    fc_tools.graphics.PlaneCoefs([0 0 1],[0 -1 1])];
colormap('jet')
fc_graphics4mesh.slice(q3,me3,u,P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k','LineWidth',2)

```

Listing 11: Using `fc_graphics4mesh.slice` function with a 3D mesh

9 `fc_graphics4mesh.sliceiso` function

The `fc_graphics4mesh.sliceiso` function displays isolines of datas on the intersection of a plane and a 3D mesh given by its vertices array q and its connectivity array me .

Syntaxe

```
fc_graphics4mesh.sliceiso(q,me,u,P)
fc_graphics4mesh.sliceiso(q,me,u,P,Name,Value, ...)
```

Description

`sliceiso (q,me,u,P)` displays isolines of data `u` on the intersection of the plane defined by $P(1)x + P(2)y + P(3)z + P(4) = 0$ and all the 3-dimensional simplices elements given by `q` and `me` arrays. To compute `P` one can use the `fc_tools.graphics.PlaneCoefs` function of the `FC-TOOLS` toolbox. The 1-by-4 array `P`, is obtained with `P=fc_tools.graphicsPlaneCoefs(Q,V)` where `Q` is a point in the plane and `V` is a vector orthogonal to it. One can also used a n -by-4 array `P` where each line define a plane.

`sliceiso (q,me,u,P,Name,Value, ...)` allows additional key/value pairs to be used when displaying `u`. The key strings could be


- '`niso`' : to specify the number of isolines (default : 10)
- '`isorange`' : to specify the list of isovalues (default : empty)
- '`color`' : to specify one color for all isolines (default : empty)
- '`isocolorbar`' : if true display a colorbar. Default is false.
- '`format`' : to specify the format of the isovalues print in the colorbar. Default is '`%g`'.
- '`mouse`' : if `true`, display information on clicked isoline (default : `true`)

For key strings, one could also used any options of the `plot3` function.

This function accepts until 4 output arguments :

- 1st output is the colors of the isolines
- 2nd output is the isovalues of the isolines
- 3th output is the handle of the colobar iso.
- 4th output is all the handles of the isolines as an 2D-array of dimension `N`-by-`niso`, where `N` is the number of elementary meshes where isolines are drawn.

3D example : the following code is part of the `fc_graphics4mesh.demos.sliceiso3D` function.



```

u=@(x,y,z) 2*cos(x).*sin(y+z);
[q3,me3,toGlobal3]=fc_meshTools.simplicial.getMeshArrays('3D',3);
U3=fc_meshTools.eval(u,q3);
[q1,me1,toGlobal1]=fc_meshTools.simplicial.getMeshArrays('3D',1);

figure(1)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 -1 1]);
fc_graphics4mesh.slicemesh(q3,me3,P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
fc_graphics4mesh.sliceiso(q3,me3,U3,P)
axis equal;axis image
view(-11,15)

figure(2)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 -1 1]);
fc_graphics4mesh.slicemesh(q3,me3,P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
fc_graphics4mesh.sliceiso(q3,me3,U3,P,'Linewidth',2, ...
    'isocolorbar',true,'LineWidth',2,'format','%3f');
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 -1 0]);
fc_graphics4mesh.slice(q3,me3,U3,P)
fc_graphics4mesh.sliceiso(q3,me3,U3,P,'color','w','LineWidth',2);
axis equal;axis image
colorbar('Location','westoutside')
caxis([min(U3),max(U3)])
view(-11,15)

figure(3)
P=fc_tools.graphics.PlaneCoefs([0 0 1],[1 0 0]); ...
    fc_tools.graphics.PlaneCoefs([0 0 1],[0 1 0]); ...
    fc_tools.graphics.PlaneCoefs([0 0 1],[0 0 1]);
fc_graphics4mesh.slicemesh(q3,me3,P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
fc_graphics4mesh.sliceiso(q3,me3,U3,P,'isocolorbar',true,'LineWidth',2, ...
    'format','%3f');
axis equal;axis image

figure(4)
P=[fc_tools.graphics.PlaneCoefs([0 0 1],[0 1 0]); ...
    fc_tools.graphics.PlaneCoefs([0 0 1],[0 -1 1])];
fc_graphics4mesh.slice(q3,me3,U3,P)
hold on
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
fc_graphics4mesh.sliceiso(q3,me3,U3,P,'Color','w','LineWidth',2);
caxis([min(U3),max(U3)])
axis equal;axis image

```

Listing 12: Using `fc_graphics4mesh.sliceiso` function with a 3D mesh

10 fc_graphics4mesh.plotquiver function

The function `fc_graphics4mesh.plotquiver` displays vector field datas on a mesh given by its vertices array `q` and its connectivity array `me`.

Syntax

```
fc_graphics4mesh.plotquiver(q,me,V)
fc_graphics4mesh.plotquiver(q,me,V,Name,Value, ...)
```

Description

`plotquiver(q,me,V)` displays vector field `u` on a simplicial mesh. The vector field data `u` can be a 1-by-dim cell arrays of handle functions or an dim-by-`n_q` array.

`plotquiver(q,me,V,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are


- `'freq'` : quiver frequencie, (default : 1)
- `'scale'` : quiver scale, (default is `fc_meshtools.getCharacteristicLength(q)/20`)
- `'color'` : set one color for all quivers (default: default color of the `quiver` or `quiver3` functions). Cannot be used with `'colordata'` option.
- `'colordata'` : each quiver is colorized with a 1-by-`nq` array or a handle function (it will evaluated in all vertices) (default : empty).

The options of second level depend on the type of mesh elements to represent.

One can use any option of the following functions according to the type of d -simplex to be represented.

- In dimension 3 and with empty `'colordata'` , the `quiver3` function is used.
- In dimension 2 and with empty `'colordata'` , the `quiver` function is used.
- In dimension 2 or 3 and with no empty `'colordata'`, the third party `fc_tools.graphics.vfield3 . vfield3` function is used.

2D example




```

v=@(x,y) y.*sqrt(x.^2+y.^2),@(x,y) -x.*sqrt(x.^2+y.^2);
vv=@(x,y) x/5,@(x,y) y/5;
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh2D(2); % Select small mesh
V2=fc_meshtools.eval(v,q2);
u2=sqrt(V2{1}.^2+V2{2}.^2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh2D(1);
V1=fc_meshtools.eval(v,q1);
VV1=fc_meshtools.eval(vv,q1);
u1=sqrt(V1{1}.^2+V1{2}.^2);
figure(1)
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q2,me2,V2,'color','Olive','freq',4,'scale',0.1)
axis image;axis off
figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q1,me1,V1,'LineWidth',2)
axis image;axis off
figure(3)
colormap('jet')
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q2,me2,V2,'colordata',u2)
axis image;axis off
colorbar
figure(4)
colormap('jet')
fc_graphics4mesh.plotmesh(q2,me2,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q1,me1,VV1,'LineWidth',2,'colordata',@(x,y) ...
    sin(x+y))
axis image;axis off
colorbar

```

Listing 13: Plot quiver on 2D mesh

3D example




```

v=@(x,y,z) cos(x+z).*sin(y),@(x,y,z) sin(x).*cos(z+y),@(x,y,z) sin(z).*cos(x+y)};
[q3,me3,toGlobal3]=fc_meshtools.simplicial.getMesh3D(3);
V3=fc_meshtools.eval(v,q3);
fu3=@(x,y,z) y;
u3=fc_meshtools.eval(fu3,q3);
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh3D(2);
V2=fc_meshtools.eval(v,q2);
u2=sqrt(V2{1}.^2+V2{2}.^2+V2{3}.^2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh3D(1);
V1=fc_meshtools.eval(v,q1);
u1=sqrt(V1{1}.^2+V1{2}.^2+V1{3}.^2);
figure(1)
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q3,me3,V3,'freq',2)
figure(2)
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q2,me2,V2)
figure(3)
colormap('jet')
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q3,me3,V3,'colordata',u3,'freq',2)
colorbar
figure(4)
colormap('jet')
fc_graphics4mesh.plotmesh(q1,me1,'color','k')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q2,me2,V2,'colordata',u2),'scale',1)

```

Listing 14: Plot quivers on 3D mesh

3D surface example



```

v={@(x,y,z) cos(x+z).*sin(y),@(x,y,z) sin(x).*cos(z+y),@(x,y,z) sin(z).*cos(x+y)};
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMesh3Ds(2);
V2=fc_meshtools.eval(v,q2);
u2=sqrt(V2{1}.^2+V2{2}.^2+V2{3}.^2);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMesh3Ds(1);
V1=fc_meshtools.eval(v,q1);
u1=sqrt(V1{1}.^2+V1{2}.^2+V1{3}.^2);
figure(1)
fc_graphics4mesh.plotmesh(q1,me1,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q2,me2,V2)
axis image;axis off
figure(2)
fc_graphics4mesh.plotmesh(q1,me1,'color','LightGray')
hold on
fc_graphics4mesh.plotquiver(q1,me1,V1,'LineWidth',2)
axis image;axis off
figure(3)
colormap('jet')
fc_graphics4mesh.plotmesh(q1,me1,'color','LightGray')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q2,me2,V2,'colordata',u2)
colorbar
figure(4)
colormap('jet')
fc_graphics4mesh.plotmesh(q1,me1,'color','LightGray')
hold on;axis image;axis off
fc_graphics4mesh.plotquiver(q1,me1,V1,'LineWidth',2,'colordata',u1, 'scale',0.2)
colorbar

```

Listing 15: 3D surface mesh : `plotquiver` function

11 `fc_graphics4mesh.plotnodes` function

The function `fc_graphics4mesh.plotnodes` displays the nodes of a given mesh nodes array

Syntaxe

```
fc_graphics4mesh.plotnodes(q)
fc_graphics4mesh.plotnodes(q,Name,Value, ...)
```

Description

plotnodes(q) displays all the nodes of the array **q** with a specific marker.


plotnodes(q,Name,Value, ...) specifies options using one or more **Name,Value** pair arguments. Options of first level are

- '**Marker**' : to specify the marker (default : '.'),
- '**MarkerSize**' : to specify the marker size (default : 6),
- '**idx**' : to specify indices of the nodes to be displayed,

The options of second level depend on the dimension :

- if dimension 2, then options are those of the **plot** function,
- if dimension 3, then options are those of the **plot3** function.

2D example : the following code is part of the **fc_graphics4mesh.demos.plotnodes2D** function.




```
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMeshArrays('2D',2,true);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('2D',1,true);
figure(1)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotnodes(q2)
axis image;axis off


figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'Color','k')
fc_graphics4mesh.plotnodes(q1,'Color','r','MarkerSize',10,'Marker','s')
```

Listing 16: Using **fc_graphics4mesh.plotnodes** function with a 2D mesh

3Ds example : the following code is part of the **fc_graphics4mesh.demos.plotnodes3Ds** function.



3D example : the following code is part of the `fc_graphics4mesh.demos.plotnodes3D` function.



12 `fc_graphics4mesh.plotnodesidx` function

The function `fc_graphics4mesh.plotnodesidx` displays indices of the given mesh nodes array

Syntax

```

fc_graphics4mesh.plotnodesidx(q,)
fc_graphics4mesh.plotnodesidx(q,Name,Value, ...)

```

Description


`plotnodesidx(q)` displays all the numbers/indices of the nodes array `q`

`plotnodesidx(q,Name,Value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- '`toGlobal`' : to specify other indices to display,
- '`idx`' : to select particular indices.

The options of second level are those of the `text` function.

2D example : the following code is part of the `fc_graphics4mesh.demos.plotnodesidx2D` function.




```
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMeshArrays('2D',2,true);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('2D',1,true);
figure(1)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'Color','k')
fc_graphics4mesh.plotnodesidx(q2)
axis image;axis off


figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'Color','k')
fc_graphics4mesh.plotnodesidx(q1,'Color','b','backgroundcolor','Salmon',...
'edgecolor','purple','fontsize',7)
```

Listing 19: Using `fc_graphics4mesh.plotnodesidx` function with a 2D mesh

3Ds example : the following code is part of the `fc_graphics4mesh.demos.plotnodesidx3Ds` function.



3D example : the following code is part of the `fc_graphics4mesh.demos.plotnodesidx3D` function.



13 `fc_graphics4mesh.plotelementsidx` function

The function `fc_graphics4mesh.plotelementsidx` displays indices of a given mesh connectivity array

Syntaxe

```

fc_graphics4mesh.plotelementsidx(q,me)
fc_graphics4mesh.plotelementsidx(q,me,Name,Value, ...
    ...)

```

Description


plotelementsidx(q,me) displays all the numbers/indices of the connectivity array `me`.

plotelementsidx(q,me,Name,Value, ...) specifies function options using one or more `Name,Value` pair arguments. Options of first level are

- '`toGlobal`' : to specify other indices to display,
- '`idx`' : to select particular indices.

The options of second level are those of the `text` function.

2D example : the following code is part of the `fc_graphics4mesh.demos.plotelementsidx2D` function.




```
[q2,me2,toGlobal2]=fc_meshtools.simplicial.getMeshArrays('2D',2,true);
[q1,me1,toGlobal1]=fc_meshtools.simplicial.getMeshArrays('2D',1,true);
figure(1)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotelementsidx(q2,me2)
axis image;axis off


figure(2)
fc_graphics4mesh.plotmesh(q2,me2,'Color','LightGray')
hold on
fc_graphics4mesh.plotmesh(q1,me1,'Color','k')
fc_graphics4mesh.plotelementsidx(q1,me1,'Color','b',...
'BackgroundColor','Moccasin','FontSize',5,'edgecolor','k')
```

Listing 22: Using `fc_graphics4mesh.plotelementsidx` function with a 2D mesh

3Ds example : the following code is part of the `fc_graphics4mesh.demos.plotelementsidx3Ds` function.



3D example : the following code is part of the `fc_graphics4mesh.demos.plotelementstidx3D` function.



Informations for git maintainers of the Matlab toolbox

git informations on the toolboxes used to build this manual

```
-----  
name : fc-graphics4mesh  
tag : 0.1.2  
commit : e922041e090275b69207ed6d4fb52df06f5e3fba  
date : 2020-03-07  
time : 16-09-48  
status : 0  
-----  
name : fc-tools  
tag : 0.0.31  
commit : 3a25f08630ff69e7f8ef4ab451671e454c492e36  
date : 2020-02-23  
time : 11-27-44  
status : 0  
-----  
name : fc-bench  
tag : 0.1.2  
commit : 666dc60d1277f5fa9c99dee4ae1c33270f22c57d  
date : 2020-02-16  
time : 06-38-46  
status : 0  
-----  
name : fc-amat  
tag : 0.1.2  
commit : 957340f6e71d805dbd8b9d04c434b24fd3f92591  
date : 2020-02-16  
time : 06-39-42  
status : 0  
-----  
name : fc-meshtools  
tag : 0.1.3  
commit : cdbc41bc98af4e4facc1746024aced1f21aae53  
date : 2020-02-17  
time : 10-52-56  
status : 0  
-----
```

git informations on the L^AT_EX package used to build this manual

```
-----  
name : fctools  
tag :  
commit : 57968c4a96c2593cccc9da9efd3e52b2ff012cb5  
date : 2020-02-07  
time : 06:41:09  
status : 1  
-----
```

Using the remote configuration repository:

```
url      ssh://lagagit/MCS/Cuvelier/Matlab/fc-config  
commit  5e45f254c19250ff5077a8477825e6c975245689
```