



fc-tools Matlab toolbox, User's Guide*

version 0.0.31

François Cuvelier[†]

March 19, 2020

Abstract

The fc-tools Matlab toolbox contains some basic tools used in my other toolboxes.

*LATEX manual, revision 0.0.31, compiled with Matlab 2019a, and toolbox fc-tools[0.0.31].
†LAGA, UMR 7539, CNRS, Université Paris 13 - Sorbonne Paris Cité, Université Paris 8,
99 Avenue J-B Clément, F-93430 Villetaneuse, France, cuvelier@math.univ-paris13.fr
This work was partially supported by the ANR project DEDALES under grant ANR-14-CE23-0005.

0 Contents

1	graphics module	3
1.1	main functions	3
1.2	xcolor submodule	6
1.3	monitors submodule	8
1.4	gptoolbox submodule	11
1.5	crop submodule	11
1.6	vfield3 submodule	11
2	utils module	11
3	sys module	12

1 graphics module


1.1 main functions

1.1.1 `fc_tools.graphics.display_rgb` function

The `fc_tools.graphics.display_rgb` displays colors of a n -by-3 RGB colors array with their names if available.

Syntaxe

```
fc_tools.graphics.display_rgb(rgb)
fc_tools.graphics.display_rgb(rgb, names)
```



1.1.2 `fc_tools.graphics.selectColors` function

The `fc_tools.graphics.selectColors` function returns colors that are maximally perceptually distinct without using the Image Processing Toolbox.

This function is inspired by the function `select_colors` (or `distinguishable_colors`) of *Timothy E. Holy* which uses the Image Processing Toolbox of Matlab.

Syntaxe


```
colors=fc_tools.graphics.selectColors(N)
colors=fc_tools.graphics.selectColors(N, ...
    key, value)
```


Description

`colors=fc_tools.graphics.selectColors(N)` Returns N colors that are maximally perceptually distinct as a N -by-3 RGB colors array.

`colors=fc_tools.graphics.selectColors(N, Name, Value)` specifies function options using one or more `Name,Value` pair arguments. Options are

- `'background'` : the N colors selected will be as far as possible from the colors specified by this options as a n -by-3 RGB colors array. Default is `[1 1 1; 0 0 0; 0.8 0.8 0.8;1,0,1]`
- `'func'` : To specify an other function for converting RGB colors to LAB colors. Default is local `RGB2LAB` function.





```

colors=fc_tools.graphics.selectColors(6);
x=0:pi/100:2*pi;
figure(1)
plot(x,cos(x),'color',colors(1,:),'Linewidth',1.5)
hold on
plot(x,sin(x),'color',colors(2,:),'Linewidth',1.5)
plot(x,cos(2*x),'color',colors(3,:),'Linewidth',1.5)
plot(x,sin(2*x),'color',colors(4,:),'Linewidth',1.5)
plot(x,cos(3*x),'color',colors(5,:),'Linewidth',1.5)
plot(x,sin(3*x),'color',colors(6,:),'Linewidth',1.5)
legend('cos(x)', 'sin(x)', 'cos(2x)', 'sin(2x)', 'cos(3x)', 'sin(3x)')

```

Listing 3: `fc_tools.graphics.xcolor.selectColors` function

1.1.3 `fc_tools.graphics.DisplayFigures` function

The `fc_tools.graphics.DisplayFigures` function regularly distributes the figures on the screen.

Syntaxe

```

fc_tools.graphics.DisplayFigures()
fc_tools.graphics.DisplayFigures(n)
fc_tools.graphics.DisplayFigures('nfig',n)

```

Without argument, all figures are regularly distributed on the screen. Otherwise, empty figures with numbers **1** to **n** are created and regularly distributed on the screen.

1.1.4 `fc_tools.graphics.SaveAllFigsAsFiles` function

The `fc_tools.graphics.SaveAllFigsAsFiles` saves all figures as files.

Syntaxe

```

fc_tools.graphics.SaveAllFigsAsFiles(basename)

```

```
fc_tools.graphics.SaveAllFigsAsFiles(file, ...
    key, value, ...)
```

Description

`fc_tools.graphics.SaveAllFigsAsFiles(basename)` save each figure in the file
[basename, '_fig', fignum]

of the current directory where `fignum` is the number of the figure to be saved.

`fc_tools.graphics.SaveAllFigsAsFiles(file, key, value, ...)` specifies function options using one or more `Name,Value` pair arguments. Options are

- '`format`' : to specify the file format. `Value` could be '`epsc`' (default), '`pdf`', '`png`' or '`pdflatex`'.
- '`dir`' : to specify the directory (default '`.`'). the directory is created if it does not exist.
- '`verbose`' : if `true`, prints file names. Default is `false`.
- '`tag`' : if `true` each figure is saved in the file:

[basename, '_fig', fignum, '_', software, version]

where `software` is Matlab and `version` is its release. Default is `false`.

- '`size`' : to specify size of the image. Default is [800,600].

1.2 xcolor submodule

1.2.1 `fc_tools.graphics.xcolor.svg` function

The `fc_tools.graphics.xcolor.svg` function returns names and RGB values of the 149 SVG colors.

Syntax

```
[name,rgb]=fc_tools.graphics.xcolor.svg()
```

`name` is cell array of string (color names) and `rgb` is 149-by-3 array (rgb values) such that the color `name{i}` has `rgb(i,:)` for rgb values.

1.2.2 `fc_tools.graphics.xcolor.X11` function

The `fc_tools.graphics.xcolor.X11` function returns names and RGB values of the 317 X11 colors.

Syntax

```
[name,rgb]=fc_tools.graphics.xcolor.X11()
```

`name` is cell array of string (color names) and `rgb` is 317-by-3 array (rgb values) such that the color `name{i}` has `rgb(i,:)` for rgb values.

1.2.3 `fc_tools.graphics.xcolor.fullX11` function

The `fc_tools.graphics.xcolor.fullX11` function returns names and RGB values of the 738 X11 colors.

Syntaxe

```
[name,rgb]=fc_tools.graphics.xcolor.fullX11()
```


`name` is cell array of string (color names) and `rgb` is 738-by-3 array (rgb values) such that the color `name{i}` has `rgb(i,:)` for rgb values.

1.2.4 `fc_tools.graphics.xcolor.display_colors` function

The `fc_tools.graphics.xcolor.display_colors` function displays SVG colors, X11 colors and (full)X11 colors.

Syntaxe

```
fc_tools.graphics.xcolor.display_colors()
```



1.3 monitors submodule

1.3.1 `fc_tools.graphics.monitors.onGrid` function

The `fc_tools.graphics.monitors.onGrid` displays figures on a virtual m -by- n grid (as `subplot` command with axes) positioned on a selected monitor.

Syntax

```
fc_tools.graphics.monitors.onGrid(n,m)
fc_tools.graphics.monitors.onGrid(n,m, ...
    key,value, ...)
```

Description


`fc_tools.graphics.monitors.onGrid(n,m)`

A virtual m -by- n grid is created on the first monitor and the figures num-

bered from 1 to $m \times n$ are moved or created (if it doesn't exist) respectively to the position given by an index (default is the figure number). This index runs row-wise; all columns of the first row are numbered from left to right and so on with rows 2 to m .

`fc_tools.graphics.monitors.onGrid(n,m, key,value)` specifies function options using one or more `key,value` pair arguments. Options are

- `'figures'` : specifies the numbers of the figures to be used. Default is `1:m*n`.
- `'positions'` : specifies the index on the grid corresponding to the `'figures'` option. Default is `1:m*n`.



```

1  x=0:pi/100:2*pi;
2  close all
3  fc_tools.graphics.monitors.onGrid(2,3,'figures',[1,3], ...
4    'positions',[2,6],'covers',4/5)
5  figure(1)
6  plot(x,sin(x))
7  figure(3)
8  plot(x,cos(x))
9  fc_tools.graphics.monitors.onGrid(2,3,'figures',[2,4], ...
10   'positions',[1,5],'covers',4/5)
11 figure(2)
12 plot(sin(x),cos(x))
13 axis equal
14 figure(4)
15 plot(2*sin(x),cos(x))
16 axis equal
17 fprintf('waiting 2s...\n');pause(2)
18 fc_tools.graphics.monitors.onGrid(2,2,'figures',1:4,'covers',4/5, ...
19   'location','NorthWest')

```

Listing 5: Using `fc_tools.graphics.monitors.onGrid` function, part of `fc_tools.graphics.monitors.demos.demo02` function. Figures are screenshot taken at line 15 (left) and after last line (right).

1.3.2 `fc_tools.graphics.monitors.show` function

The `fc_tools.graphics.monitors.show` displays monitors with their resolution, position and number on a figure. When arguments are provided, they are those of the `fc_tools.graphics.monitors.onGrid` function and then the grid is also drawn with the indices of the positions of the grid elements.

Syntaxe

```

fc_tools.graphics.monitors.show()
fc_tools.graphics.monitors.show(n,m)
fc_tools.graphics.monitors.show(n,m, ...

```

```
key,value,...)
```

Description

fc_tools.graphics.monitors.show()


Displays monitors with their resolution, position and number on a figure.

fc_tools.graphics.monitors.show(n,m)

Add the **m**-by-**n** grid on the figure created by the **fc_tools.graphics.monitors.show()** command to to preview positions of figures created or moved by the **fc_tools.graphics.monitors.onGrid(n,m)** command.


fc_tools.graphics.monitors.show(n,m, key,value)

specifies function options using one or more **key,value** pair arguments.
Options are those of the **fc_tools.graphics.monitors.onGrid** function.



```
1 close all
2 nM=fc_tools.graphics.monitors.number();
3 figure(1)
4 fc_tools.graphics.monitors.show(3,3,'monitor',1,'covers',1)
5 if nM>=2
6 figure(2)
7 fc_tools.graphics.monitors.show(4,3,'monitor',2, ...
8 'location','east','covers',3/4)
9 end
10 if nM>=3
11 figure(3)
12 fc_tools.graphics.monitors.show(3,2,'monitor',3, ...
13 'location','topleft','covers',3/4)
14 end
```

Listing 6: Using **fc_tools.graphics.monitors.show** function, part of
fc_tools.graphics.monitors.demos.demo03 function on a computer with two monitors.



1.4 gptoolbox submodule

This submodule contains some files of the **gptoolbox** from *Alec Jacobson* (see <https://github.com/alecjacobson/gptoolbox>)

1.5 crop submodule

This submodule contains the function `crop` from *Andrew Bliss*.

1.6 vfield3 submodule

This submodule contains the function `vfield3` from *M MA* (see <https://www.mathworks.com/matlabcentral/fileexchange/8653-vfield3>)

2 utils module

- `fc_tools.utils.deleteCellOptions` deletes specified key/value pairs in a cell array of key/value pairs.
- `fc_tools.utils.isfunHandle` test if the input argument is a function handle.
- `fc_tools.utils.funHandleName` test if the input argument is a function handle.
- `fc_tools.utils.fun2str ...`

3 sys module

- `fc_tools.sys.getComputerName()` returns the name of the computer as a string.
- `fc_tools.sys.getUserName()` returns the name (login) of the current user as a string.
- `fc_tools.sys.getRAM()` returns available memory (RAM) in GB of the computer.
- `fc_tools.sys.getCPUinfo()` returns CPU(s) informations as a structure.
- `fc_tools.sys.getOSinfo()` returns OS informations as a structure.
- `fc_tools.sys.isfolder()` return true if a folder exists.
- `fc_tools.sys.isfileexists()` return true if a file exists.

In Listing 8, some examples are provided.

```
Listing 8: : example using fc_tools.sys functions
_____
printf('RAM: %.2f GB\n',fc_tools.sys.getRAM())
CPU= fc_tools.sys.getCPUinfo()
OS=fc_tools.sys.getOSinfo()
```

```
Output
_____
RAM : 62.59 GB
CPU =
    struct with fields:
        name: 'Intel(R) Core(TM) i9-7940X CPU @ 3.10GHz'
        nthreadspercore: 2
        ncoreperproc: 14
        nprocs: 1

OS =
    struct with fields:
        distributor: 'Ubuntu'
        description: 'Ubuntu 18.04.4 LTS'
        release: '18.04'
        codename: 'bionic'
        arch: 'x86_64'
        shortname: 'Ubuntu'
```

Informations for git maintainers of the Matlab toolbox

git informations on the toolboxes used to build this manual

```
-----  
name : fc-tools  
tag : 0.0.31  
commit : 5f136a7a027bcb54b408a8b16be8767a0b6239de  
date : 2020-03-19  
time : 04:49:37  
status : 0  
-----
```

git informations on the L^AT_EX package used to build this manual

```
-----  
name : fctools  
tag :  
commit : 57968c4a96c2593cccc9da9efd3e52b2ff012cb5  
date : 2020-02-07  
time : 06:41:09  
status : 1  
-----
```

Using the remote configuration repository:

```
url      ssh://lagagit/MCS/Cuvelier/Matlab/fc-config  
commit   ca2a4f11eb918d3020f934e3545abef8b49ef3e8
```